




101402

## RING MEDIUM

Designed by  
NAVA + AROSIO

Floodlight for outdoor installation on a façade/wall, with 355° swivel base and allowing horizontal adjustment of +90° / -40°. Phospho-chromatised and polyester powder coated die-cast copper-free aluminium base and head, tempered safety glass, moulded silicone gaskets and o-rings, with screws in stainless steel. Swivel joint with graduated scale and mechanical aiming lock. Built-in LED driver, with 1 COB CREE "CXB 1512" LED. IP66 rating.



| light source                | light beam options | lumen output (lm) | lumin. efficacy (lm/w) |
|-----------------------------|--------------------|-------------------|------------------------|
| <b>3000°K warm-white</b>    |                    |                   |                        |
| cob led                     | 14°                | 1.900             | 118.75                 |
| cob led                     | 35°                | 1.813             | 113.31                 |
| cob led                     | 55°                | 1.722             | 107.62                 |
| <b>4000°K neutral-white</b> |                    |                   |                        |
| cob led                     | 14°                | 2.000             | 125.00                 |
| cob led                     | 35°                | 1.900             | 118.75                 |
| cob led                     | 55°                | 1.805             | 112.81                 |

### Finish color options:

Textured Grey  
RAL 9006

Anthracite Grey  
RAL 7016

Matt Black  
(on request)

### Technical features



### Technical data

|              |  |
|--------------|--|
| Wattage      | 16 WATT  |
| IP Rating    | IP66   |
| IK Rating    | IK10   |
| Material     | High corrosion resistance die-cast copper-free aluminum body |
| Coating      | Polyester powder coating with phosphochromating pre-finish   |
| Light source | NR. 1 COB CREE "CXB 1512" LED                                |
| Screws       | Stainless steel  |
| Transformer  | Electronic power supply 220/240V 50/60Hz built-in            |
| Gasket       | Silicone rubber  |
| Glass        | Tempered   |
| Cable gland  | M16 rubber grommet   |
| Power cable  | 1 mt. power cable included                                   |
| Gross weight | 2,50 Kg  |

## OTHER VIEW




## OPTIONAL

AC044  
SPIKE



AC048  
HONEYCOMB LOUVER



AC038  
TREE STRAP  
FOR RING SERIES




## OPTIONAL

LUMINAIRE SUITABLE FOR POLE MOUNTING  
IN SINGLE OR MULTIPLE COMBINATIONS

## OPTIONAL LIGHT DISTRIBUTIONS

These optional light distributions are obtained with special glass diffusers, product must be ordered as per light distribution requirement and these optics are not interchangeable

ELLIPTICAL



PRISMATIC

