

NOVELTY



Sistema modulare in alluminio estruso sottoposto a curvatura con raggio 500mm e 1000mm disponibile in versione sospensione e incasso a scomparsa, per creare anelli o composizioni miste di linee e curve su soffitto o parete. Sorgente luminosa composta da modulo LED a luce diretta e dimmerazione inserita nel rosone o in remoto. Finitura con vernice poliacrilica in bianco e finitura laterale del profilo a coste. Schermo in policarbonato opale estruso e curvato. Ideale per uffici, hall, zone living, grandi spazi.

Modular system in extruded curved aluminum with 500mm and 1000mm radius. Available in trimless recessed and suspension offering the possibility to create rings or mixed compositions of lines and curves. Light source made of LED module with direct light and version with dimmable driver. Polyacrylic white painted and ribbed lateral finish. Curved extruded opal polycarbonate diffuser. Ideal for offices, hall, living areas, and large areas.


PAGE CATALOGUE 46

CODICE CODE

DEGREES

FONTI LUMINOSE LIGHT SOURCES



Kgn



L23101.360.0102

360°


Potenza assorbita apparecchio / Luminaire power consumption 56W
Flusso luminoso apparecchio / Luminaire luminous flux 2130 lm
3000K Ra 80 220-240V DALI / PUSH DIM



L23201.360.0102

360°

Potenza assorbita apparecchio / Luminaire power consumption 109W
Flusso luminoso apparecchio / Luminaire luminous flux 4260 lm
3000K Ra 80 220-240V DALI / PUSH DIM



Fotometrie e Classi Energetiche disponibili www.panzeri.it / Photometric data and Energy Label available at www.panzeri.it

CODICI COLORI DISPONIBILI / COLOUR CODES AVAILABLE

01 Bianco
White

Brooklyn Round_

design_Enzo Panzeri 2017


LED CE IP40

CODICE
CODE

DEGREES

FONTI LUMINOSE
LIGHT SOURCES


Kgn



L23101.180.0102

180°



Potenza assorbita apparecchio / Luminaire power consumption 29W
Flusso luminoso apparecchio / Luminaire luminous flux 1065 lm
3000K Ra 80 220-240V DALI / PUSH DIM



L23201.180.0102

180°

Potenza assorbita apparecchio / Luminaire power consumption 56W
Flusso luminoso apparecchio / Luminaire luminous flux 2130 lm
3000K Ra 80 220-240V DALI / PUSH DIM



Fotometrie e Classi Energetiche disponibili www.panzeri.it / Photometric data and Energy Label available at www.panzeri.it

CODICI COLORI DISPONIBILI / COLOUR CODES AVAILABLE

01 Bianco
White