


## EDNA 1,2,3,4,5 WITH INCANDESCENT LAMPS

**Applications:** housing constructions (rooms, corridors), cultural premises

**Assembly:** to the ceiling or on the wall



### Technical data:

Light source	Incandescent lamp
Input voltage	230V
IP	IP 43
Fixtures	Sheet steel modified by powder painting
Shade	Three-layer, hand blown glass - TRIPLEX OPAL matt
Shade attachment	With two-step clamp holders

### Variants:

	Type	Diameter x Height [mm]	Input [W]	Socket
EDNA 1	IN-12K2/020	220x105	60	E27
EDNA 2	IN-12K52/022	280x105	100	E27
	IN-22K52/022		2x60	2xE27
EDNA 3	IN-12K63/024	350x105	100	E27
	IN-22K63/024		2x75	2xE27
EDNA 4	IN-22K74/026	420x115	2x75	2xE27
EDNA 5	IN-32K88/028	490x115	3x60	3xE27

### Assembly dimensions:

	Diameter fixture [mm]	A [mm]	B [mm]	C [mm]	D [mm]
EDNA 1	173	122	60	36,5	33
EDNA 2	228	130	130	3	91
EDNA 3	275	165	165	0	105
EDNA 4	324	190	190	0	108
EDNA 5	372	220	220	0	144

