



## ELSA 1,2,3,4,5,6 - INCANDESCENT LAMPS

**Applications:** housing constructions (rooms, corridors), cultural premises

**Mounting:** ceiling or wall



### Technical data:

Light source	Incandescent lamp
Input voltage	230V
IP	IP 44 (BT), IP20 (B)
Energy class	By source
Fixtures	Sheet steel modified by powder painting
Shade	Three-layers, hand blown glass - TRIPLEX OPAL with matt surface
Shade attachment	Bayonet

### Variants:

	Type	ØA1xÅ2 [mm]	Input [W]	Socket
ELSA 1	IN-12BT12/023	250x84	75	E27
ELSA 2	IN-12BT13/025	300x86	100	E27
	IN-22BT13/025		2x60	2xE27
ELSA 3	IN-12BT14/027	360x88	100	E27
	IN-22BT14/027		2x75	2xE27
ELSA 4	IN-22BT15/029	420x90	2x75	2xE27
ELSA 5	IN-32BT16/626	500x92	3x60	3xE27
ELSA 6	IN-32BT17/627	590x94	3x75	3xE27

### Mounting dimensions:

	ØA [mm]	B [mm]	C [mm]	D [mm]	E [mm]	F [mm]
ELSA 1	198	142	41	82	66	10
ELSA 2	243	180	52	104	87	10
ELSA 3	293	221	64	128	109	15
ELSA 4	344	251	73	145	123	15
ELSA 5	414	303	87,5	175	170	10
ELSA 6	465	346	100	200	175	0

