



HANDY 750 IP21 11W/830 1200LM WH

A range of surface-mounted LED luminaires for the general lighting of worktops in kitchens and utility rooms. The luminaires have a built-in on/off switch can be used to control each light separately, and a two-part earthed socket. The handedness of the socket can be changed for either right-handed or left-handed installation. Four different lengths are available.



Housing material	BODY MADE OF ALUMINIUM
Diffuser material	DIFFUSER MADE OF POLYCARBONATE
Mounting and IP class	SURFACE MOUNT
Coupling: chainable	LINKABLE
Cut off / mm	3x2,5mm ²
Coupling: connector type	SPRING CONNECTORS
LED-module lifetime L70	40 000H

PRODUCT CODE	GTIN1	 P x K x L	TYPE OF PACKAGING	PRODUCT FAMILY
HANDY 750 IP21 11W/830 1200LM WH				
4118724	6435200219213	52 x 74 x 750	Shelf packaging	HANDY

TECHNICAL DATAS (ETIM)			
ETIM class	EC002892	Nominal voltage (max) (V)	230
Type of dimming	Not dimmable	Nominal voltage (min) (V)	230
Voltage type	AC	Length (mm)	750
Height/depth (mm)	52	Colour housing	White
Degree of protection (IP)	IP21	Suitable for surface mounting	Yes
Material housing	Aluminium	Protection class	I
Circuit	Parallel-compensated	Material cover	Plastic, opal
Ambient temperature (max) (°C)	45	System power (W)	11
Ambient temperature (min) (°C)	-30	Effective luminous flux (lm)	1200
Lamp power (W)	11	Colour temperature (max) (K)	3000
Lamp type	LED not exchangeable	Colour temperature (min) (K)	3000
Width (mm)	74	Colour rendering index CRI	80-89
Type of control gear	LED operating device current-controlled		

