


NÄSBY IP54 2X6W/830 ANT

A multipurpose LED wall luminaire for indoor and outdoor use that shines up and down. Suitable for stairways, hallways and facades, among other locations. Adjust the width of the beam of light from 0° to 80° in up and down directions.



Housing material	BODY MADE OF ALUMINIUM/ POLYCARBONATE
Diffuser material	DIFFUSER MADE OF POLYCARBONATE
Mounting and IP class	SURFACE MOUNT 3x2,5mm2
Coupling: connector type	SCREW TERMINALS
LED-module lifetime L70	30 000H

PRODUCT CODE	GTIN1	 P x K x L	TYPE OF PACKAGING	PRODUCT FAMILY
NÄSBY IP54 2X6W/830 ANT				
4116460	6435200216328	110 x 150 x 190	Shelf packaging	NÄSBY

TECHNICAL DATAS (ETIM)			
ETIM class	EC002892	Type of control gear	LED operating device current-controlled
Energy efficiency class	A	Nominal voltage (max) (V)	230
Type of dimming	Not dimmable	Nominal voltage (min) (V)	230
Voltage type	AC	Length (mm)	95
Height/depth (mm)	134	Colour housing	Anthracite
Degree of protection (IP)	IP54	Suitable for surface mounting	Yes
Material housing	Aluminium	Protection class	I
Circuit	Parallel-compensated	System power (W)	12
Ambient temperature (max) (°C)	35	Effective luminous flux (lm)	860
Ambient temperature (min) (°C)	-20	Suitable for number of lamps	2
Lamp power (W)	6	Colour temperature (max) (K)	3000
Lamp type	LED not exchangeable	Colour temperature (min) (K)	3000
Width (mm)	137	Colour rendering index CRI	80-89

