



# ELSA 3

<b>Dimensions:</b>	ø 360 mm
<b>Color:</b>	white
<b>Type:</b>	wall or ceiling mounted
<b>Shade:</b>	handmade three-layer glass TRIPLEX OPAL (matt finish)
<b>Shade attach.:</b>	bayonet
<b>Fixture:</b>	powder coated steel sheet
<b>Equipment:</b>	STANDARD, LED



## Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
<b>Classic</b>								
44798	IN-12B14/027	IP20		100	E27		2,6	24
44799	IN-22B14/027	IP20		2x75	2xE27		2,7	24
44803	E-25B14/027	IP20		2x18	2xG24q2		3,0	24
44804	E-26B14/027	IP20		2x26	2xG24q3		3,0	24
44814	IN-12BT14/027	IP44		100	E27		2,8	24
44815	IN-22BT14/027	IP44		2x75	2xE27		2,8	24
44819	E-25BT14/027	IP44		2x18	2xG24q2		3,1	24
44820	E-26BT14/027	IP44		2x26	2xG24q3		3,1	24
<b>Sensor</b>								
44807	IN-12B14/027 HF	IP20		75	E27		2,7	24
44823	IN-12BT14/027 HF	IP44		75	E27		2,6	24
<b>Dimmable</b>								
45883	ES-26B14/027 DALI	IP20		2x26	2xG24q3		3,0	24
45885	ES-26BT14/027 DALI	IP44		2x26	2xG24q3		3,1	24
<b>Emergency combined</b>								
44811	NKC-218/13/027	IP20		2x18	2xG24q2	1	3,7	24
44812	NKC-226/13/027	IP20		2x26	2xG24q3	1	3,7	24
44827	NKC-218/13/T/027	IP44		2x18	2xG24q2	1	3,8	24
44828	NKC-226/13/T/027	IP44		2x26	2xG24q3	1	3,8	24

## LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
<b>Classic</b>									
59076	LED-1L14C03BT14/027 3000	IP44	3000	15	2000	1400		3,1	60
51309	LED-1L14B07BT14/027 3000	IP44	3000	20	2590	1810		3,4	60
59576	LED-1L14C03BT14/027 4000	IP44	4000	15	2110	1480		3,1	60
51809	LED-1L14B07BT14/027 4000	IP44	4000	20	2700	1890		3,4	60
<b>Sensor</b>									
59077	LED-1L14C03BT14/027 HF 3000	IP44	3000	15	2000	1400		3,1	60
51315	LED-1L14B07BT14/027 HF 3000	IP44	3000	20	2590	1810		3,4	60
59577	LED-1L14C03BT14/027 HF 4000	IP44	4000	15	2110	1480		3,1	60
51815	LED-1L14B07BT14/027 HF 4000	IP44	4000	20	2700	1890		3,4	60
<b>Dimmable</b>									
59078	LED-1L14C03BT14/027 DALI 3000	IP44	3000	15	2000	1400		3,1	60
51313	LED-1L14B07BT14/027 DALI 3000	IP44	3000	20	2590	1810		3,4	60
59578	LED-1L14C03BT14/027 DALI 4000	IP44	4000	15	2110	1480		3,1	60
51813	LED-1L14B07BT14/027 DALI 4000	IP44	4000	20	2700	1890		3,4	60
<b>Emergency combined</b>									
59081	LED-1L14C03BT14/027/NK1W 3000	IP44	3000	15	2000	1400	3	3,1	60
51317	LED-1L14B07BT14/027/NK1W 3000	IP44	3000	20	2590	1810	3	3,4	60
59581	LED-1L14C03BT14/027/NK1W 4000	IP44	4000	15	2110	1480	3	3,1	60
51817	LED-1L14B07BT14/027/NK1W 4000	IP44	4000	20	2700	1890	3	3,4	60
<b>Emergency combined + sensor</b>									
59082	LED-1L14C03BT14/027/NK1W HF 3000	IP44	3000	15	2000	1400	3	3,1	60
51319	LED-1L14B07BT14/027/NK1W HF 3000	IP44	3000	20	2590	1810	3	3,4	60
59582	LED-1L14C03BT14/027/NK1W HF 4000	IP44	4000	15	2110	1480	3	3,1	60
51819	LED-1L14B07BT14/027/NK1W HF 4000	IP44	4000	20	2700	1890	3	3,4	60
<b>Corridor</b>									
59079	LED-1L14C03BT14/027 DALI HF CORR 3000	IP44	3000	15	2000	1400		3,1	60
59080	LED-1L14B07BT14/027 DALI HF CORR 3000	IP44	3000	20	2590	1810		3,4	60
59579	LED-1L14C03BT14/027 DALI HF CORR 4000	IP44	4000	15	2110	1480		3,1	60
59580	LED-1L14B07BT14/027 DALI HF CORR 4000	IP44	4000	20	2700	1890		3,4	60