


LINA 3

Dimensions:	320x320 mm
Color:	white
Type:	wall or ceiling mounted
Shade:	handmade three-layer glass TRIPLEX OPAL (matt finish)
Shade attach.:	two-step clamp holders
Fixture:	powder coated steel sheet (IP43) or polycarbonate molding (IP43 class II)
Equipment:	STANDARD, LED



Standard

Code	Type	IP	Source	Input [W]	Socket	T [h]	m [kg]	Warranty [month]
Classic								
43047	IN-12K64/037	IP43		100	E27		3,0	24
41307	IN-22K64/037	IP43		2x75	2xE27		3,2	24
42533	E-16K64/037	IP43		26	G24q3		3,3	24
41311	E-25K64/037	IP43		2x18	2xG24q2		3,4	24
41318	IN-22DU64/037	IP43 II		2x60	2xE27		3,2	24
41321	E-16DU64/037	IP43 II		26	G24q3		3,3	24
Sensor								
46114	IN-12K64/037 HF	IP43		75	E27		3,1	24
Dimmable								
42565	ES-25K64/037 DALI	IP43		2x18	2xG24q2		3,4	24
Emergency combined								
41333	NK-E-26/037	IP43		26	G24q3	1	3,5	24

LED

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
Classic									
59179	LED-1L14C03K64/037 3000	IP43	3000	15	2000	1360		3,3	60
59183	LED-1L14B07K64/037 3000	IP43	3000	20	2590	1760		3,7	60
59679	LED-1L14C03K64/037 4000	IP43	4000	15	2110	1430		3,3	60
59683	LED-1L14B07K64/037 4000	IP43	4000	20	2700	1840		3,7	60
Sensor									
59180	LED-1L14C03K64/037 HF 3000	IP43	3000	15	2000	1360		3,3	60

Code	Type	IP	CCT [K]	Input [W]	Lum. flux of LED [lm]	Lum. flux of luminaire [lm]	T [h]	m [kg]	Warranty [month]
59184	LED-1L14B07K64/037 HF 3000	IP43	3000	20	2590	1760		3,7	60
59680	LED-1L14C03K64/037 HF 4000	IP43	4000	15	2110	1430		3,3	60
59684	LED-1L14B07K64/037 HF 4000	IP43	4000	20	2700	1840		3,7	60
Dimmable									
59181	LED-1L14C03K64/037 DALI 3000	IP43	3000	15	2000	1360		3,3	60
59185	LED-1L14B07K64/037 DALI 3000	IP43	3000	20	2590	1760		3,7	60
59681	LED-1L14C03K64/037 DALI 4000	IP43	4000	15	2110	1430		3,3	60
59685	LED-1L14B07K64/037 DALI 4000	IP43	4000	20	2700	1840		3,7	60
Emergency combined									
59187	LED-1L14C03K64/037/NK1W 3000	IP43	3000	15	2000	1360	3	3,3	60
59189	LED-1L14B07K64/037/NK1W 3000	IP43	3000	20	2590	1760	3	3,7	60
59687	LED-1L14C03K64/037/NK1W 4000	IP43	4000	15	2110	1430	3	3,3	60
59689	LED-1L14B07K64/037/NK1W 4000	IP43	4000	20	2700	1840	3	3,7	60
Emergency combined + sensor									
59188	LED-1L14C03K64/037/NK1W HF 3000	IP43	3000	15	2000	1360	3	3,3	60
59190	LED-1L14B07K64/037/NK1W HF 3000	IP43	3000	20	2590	1760	3	3,7	60
59688	LED-1L14C03K64/037/NK1W HF 4000	IP43	4000	15	2110	1430	3	3,3	60
59690	LED-1L14B07K64/037/NK1W HF 4000	IP43	4000	20	2700	1840	3	3,7	60
Corridor									
59182	LED-1L14C03K64/037 DALI HF CORR 3000	IP43	3000	15	2000	1360		3,3	60
59186	LED-1L14B07K64/037 DALI HF CORR 3000	IP43	3000	20	2590	1760		3,7	60
59682	LED-1L14C03K64/037 DALI HF CORR 4000	IP43	4000	15	2110	1430		3,3	60
59686	LED-1L14B07K64/037 DALI HF CORR 4000	IP43	4000	20	2700	1840		3,7	60