

401608 HYDROSURF MAXI RECTANGULAR LED



Rectangular wall surface-mounted luminaire for outdoor installation on a wall, no recess needed. Phosphochromatised and polyester powder coated die-cast copper-free aluminium body, tempered safety glass, moulded silicone gasket and stainless steel screws. Built-in LED driver 220-240V 50-60Hz, with 21 mid-power CREE XH-G LED. IP65 rating.

Energy Label A++

- Material: high corrosion resistance die-cast copper-free aluminum body and frame.
- Coating: polyester powder coating with phosphocromating pre-finish
- NR. 21 x CREE XH-G LED
- Electronic transformer 220/240V 50/60Hz included
- Stainless steel screws
- Silicone rubber gasket
- Tempered safety glass
- M16 rubber grommet Rutaseal® in EPDM







125 r

40 Dam

264 mm

	LIGHT SOURCE	LED COLOR*	LIGHT BEAM OPTIONS	LUMEN OUTPUT (lm)	LUMINOUS EFFICACY (lm/w)	COLORS OPTIONS
14 WATT 220-240V 50-60HZ ELECTRONIC IP65 1,70 KG UNIT GROSS WEIGHT	MID-POWER LED	3.000°K WARM-WHITE	FLOOR WASHER 180°	1.000	71.43	TEXTURED GREY MATT WHITE (ON REQUEST) MATT BLACK (ON REQUEST)