



Lampade a parete con fascia in metallo o acciaio e diffusore in vetro. Emissione di luce diretta e indiretta ottenuta da una fonte luminosa LED. Fascia metallica rifinita con vernice poliaccrilica in bianco o fascia metallica in acciaio inox lucida o satinata o decorata a mano con foglia oro. La fascia esterna non presenta viti a vista, perché fissata con meccanismo elastico. Lunghezze standard da 7 a 90 cm. Ideale per ambienti residenziali e progetti moderni e minimalistici.

Wall lamps in metal or steel cover and glass diffuser. Direct and indirect light provided by LED sources. Metal cover in white polyacrylic paint or in polished or mat stainless steel or hand-decorated golden leaf. The metal cover has no visible screws since fastened by an elastic mechanism. Standard lengths from 7 to 90 cm. Ideal for residential use and modern and minimalist projects.

PAGE CATALOGUE 136	CODICE CODE	FONTI LUMINOSE LIGHT SOURCES	Kgn
 $\frac{7.5}{3}$ $\frac{8.5}{3 \frac{1}{4}}$	A01601.007.0000	LED retrofit bulb G9 Lmax. 60mm Ø max. 17,5mm	0,50
	A01621.007.0000	max 48W G9	
	A01637.007.0000		
	A01639.007.0000		
 $\frac{7}{2 \frac{3}{4}}$ $\frac{8.5}{3 \frac{1}{4}}$ $\frac{25}{9 \frac{7}{8}}$	A01601.025.0101	Potenza assorbita apparecchio / Luminaire power consumption 13W	1,10
	A01621.025.0101	Flusso luminoso apparecchio / Luminaire luminous flux 938 lm	
	A01637.025.0101	3000K Ra 80 220-240V	
	A01639.025.0101		
 $\frac{7}{2 \frac{3}{4}}$ $\frac{8.5}{3 \frac{1}{4}}$ $\frac{25}{9 \frac{7}{8}}$	A01601.025.0102	Potenza assorbita apparecchio / Luminaire power consumption 13W	1,10
	A01621.025.0102	Flusso luminoso apparecchio / Luminaire luminous flux 938 lm	
	NOVELTY A01637.025.0102	3000K Ra 80 220-240V DALI / PUSH DIM	
	A01639.025.0102		
 $\frac{7}{2 \frac{3}{4}}$ $\frac{8.5}{3 \frac{1}{4}}$ $\frac{45.5}{18}$	A01601.045.0101	Potenza assorbita apparecchio / Luminaire power consumption 24W	1,90
	A01621.045.0101	Flusso luminoso apparecchio / Luminaire luminous flux 1876 lm	
	A01637.045.0101	3000K Ra 80 220-240V	
	A01639.045.0101		
 $\frac{7}{2 \frac{3}{4}}$ $\frac{8.5}{3 \frac{1}{4}}$ $\frac{45.5}{18}$	A01601.045.0102	Potenza assorbita apparecchio / Luminaire power consumption 24W	1,90
	A01621.045.0102	Flusso luminoso apparecchio / Luminaire luminous flux 1876 lm	
	NOVELTY A01637.045.0102	3000K Ra 80 220-240V DALI / PUSH DIM	
	A01639.045.0102		
 $\frac{8.5}{3 \frac{1}{4}}$ $\frac{9.5}{3 \frac{3}{4}}$ $\frac{61}{24}$	A01601.060.0101	Potenza assorbita apparecchio/Luminaire power consumption 35W	2,20
	A01621.060.0101	Flusso luminoso apparecchio / Luminaire luminous flux 2814 lm	
	A01637.060.0101	3000K Ra 80 220-240V	
	A01639.060.0101		
 $\frac{8.5}{3 \frac{1}{4}}$ $\frac{9.5}{3 \frac{3}{4}}$ $\frac{61}{24}$	A01601.060.0102	Potenza assorbita apparecchio/Luminaire power consumption 35W	2,20
	A01621.060.0102	Flusso luminoso apparecchio / Luminaire luminous flux 2814 lm	
	NOVELTY A01637.060.0102	3000K Ra 80 220-240V DALI / PUSH DIM	
	A01639.060.0102		
 $\frac{7}{2 \frac{3}{4}}$ $\frac{8.5}{3 \frac{1}{4}}$ $\frac{88.5}{34 \frac{7}{8}}$	A01601.090.0101	Potenza assorbita apparecchio/Luminaire power consumption 45W	3,50
	A01621.090.0101	Flusso luminoso apparecchio / Luminaire luminous flux 3752 lm	
	A01637.090.0101	3000K Ra 80 220-240V	
	A01639.090.0101		
 $\frac{7}{2 \frac{3}{4}}$ $\frac{8.5}{3 \frac{1}{4}}$ $\frac{88.5}{34 \frac{7}{8}}$	A01601.090.0102	Potenza assorbita apparecchio/Luminaire power consumption 45W	3,50
	A01621.090.0102	Flusso luminoso apparecchio / Luminaire luminous flux 3752 lm	
	NOVELTY A01637.090.0102	3000K Ra 80 220-240V DALI / PUSH DIM	
	A01639.090.0102		

Fotometrie e Classi Energetiche disponibili www.panzeri.it / Photometric data and Energy Label available at www.panzeri.it

CODICI COLORI DISPONIBILI / COLOUR CODES AVAILABLE

DISPONIBILI A RICHIESTA LED 2700K / ON REQUEST 2700K LED AVAILABLE

01 Bianco
White

21 Foglia oro
Gold leaf

37 Acciaio inox lucido
Polished stainless steel

39 Acciaio inox satinato
Mat stainless steel